

DVFS covert-channels in Zynq Ultrascale+ SoC-FPGAs

CryptArchi

30th May 2022, Porquerolles France.

Lilian BOSSUET and Carlos LARA



**LABORATOIRE
HUBERT CURIEN**

UMR • CNRS • 5516 • SAINT-ETIENNE



CryptArchi

In this talk:


- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

In this talk:

- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU


Covert channels

“A Covert Channels has the goal of enabling the flow of information between two or more parties which are barred from communicating by an overseer party.”




Covert channels - State of the Art

- D. R. E. Gnad, C. D. K. Nguyen, S. H. Gillani, M. B. Tahoori, **Voltage-based Covert Channels using FPGAs**, in: *Cryptology ePrint Archive*, Report 2019/1394, <https://ia.cr/2019/1394> (2019).
- Zynq-7000



Covert channels - State of the Art

- E. M. Benhani, L. Bossuet, **DVFS as a Security Failure of TrustZone-enabled Heterogeneous SoC**, in: *2018 25th IEEE International Conference on Electronics, Circuits and Systems (ICECS)*, 2018, pp. 489–492. doi:10.1109/ICECS.2018.8618038.
- Zynq-7000




In this talk:


- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

General architecture of SoCs

“A System on a Chip (SoC) is an heterogeneous platform, constituted by the creation of processors and hardware accelerators in the same die.”



The Zynq Ultrascale+ SoC-FPGA




* Arrows indicate who acts as the master of the transaction.


In this talk:

- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

The Zynq Ultrascale+ Power Domains




Platform Management Overview



Function	Description
Base Firmware	Initialization, Scheduler, Event Manager, IPI Manager, Error management
Power Management	Centralized power state management with support for Embedded Energy Management Interface APIs (IEEE P2415), power off/on domains/islands, manages memories and peripherals, wakeup events
FPGA Configuration Manager	Manages secure & non-secure <u>Bitstream</u> Download from Linux/U-Boot or RPU
Warm Restart Manager	Manages subsystem warm restart for software upgrade or system recovery
Functional Safety STL (Safety Software Test Library)	A collection of software safety mechanisms for detection of random hardware (HW) faults
Custom Module (Error Management)	Allows user to customize response to error conditions

- Provide centralized access to system resources
- Modular PMU SW architecture
 - Build & Initialize only what is needed
- Provide resources to be used by all modules
 - PMU Firmware Core APIs, PMU Firmware General APIs


The Zynq Ultrascale+ Clock Tree




To modify the divider registers

- **Bare metal:** Simply perform read/write operations over the address.
- **Linux:**
 - Employ the *busybox* utility to *mmap* /dev/mem
 - Employ the userspace drivers: *cpufreq*, *fclk0*, *fclk1*, *fclk2*, *fclk3*

To characterize the channel (RO counts retrieved from the PS)




To characterize the channel: moving average $n = 4$



In this talk:

- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

Attack #1: RPU to PL




Experiments: $f_1 = 375 \text{ MHz}$, $f_2 = 214 \text{ MHz}$, $f_3 = 94 \text{ MHz}$


```

for byte in message do
  for bit in byte do
    if bit then
       $f_{clk} \leftarrow f_1$ 
    else
       $f_{clk} \leftarrow f_2$ 
    end if
     $f_{clk} \leftarrow f_3$ 
  end for
end for

```




Experiments: zero errors over 12 KB



Results

- Sender: Bare metal on Cortex-R5F@533 MHz
- Transmission delay (RPU to PL, per bit): 6.82 μ s
- Transmission rate: 17.899 KBps
- Receiver: PL, 16 ROs, 8-bit output
- Sampling rate (PL): 333 MSps
- Transmission delay (PL to RPU, per sample): 620 ns
- Sampling rate (RPU): 1.613 MSps \rightarrow RPU to RPU: 17.899 KBps


Attack #2: RPU to RPU



In this talk:

- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

Attack #3: APU to PL




Experiments: $f_1 = 100 \text{ MHz}$, $f_2 = 375 \text{ MHz}$


```

for byte in message do
  for bit in byte do
    if bit then
       $f_{clk} \leftarrow f_1$ 
       $\text{usleep}(1)$ 
    else
       $f_{clk} \leftarrow f_2$ 
    end if
  end for
end for

```




Experiments: zero errors over 64 B



Results

- Sender: Linux on Cortex-A53@1.3 GHz
- Transmission delay (APU to PL, per bit): $676 \mu s$ ($627 \mu s$, $676 \mu s$)
- Transmission rate: 185 Bps
- Receiver: PL, 16 ROs, 8-bit output
- Sampling rate (PL): 333 MSps
- Transmission delay (PL to RPU, per window): 620 ns
- Sampling rate (PS): 1.613 MSps \rightarrow APU to RPU: 185 Bps


Attack #4: APU to RPU, using the API




In this talk:

- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU

Attack #4: APU to RPU, using /dev/mem




Experiments: $f_1 = 190 \text{ MHz}$, $f_2 = 135 \text{ MHz}$, $f_3 = 300 \text{ MHz}$




Results

- Sender: Linux on Cortex-A53@1.3 GHz
- Transmission delay (APU to REG, per bit): $< 1 \mu s$
- Transmission rate: ~ 122 KBps
- Receiver: Bare metal on Cortex-R5F@533 MHz
- Sampling rate (PL): 620 ns
- Sampling rate (RPU): ~ 1.613 MSps \rightarrow APU to RPU: 122 KBps

Attack #4: APU to RPU, register-register




Experiments: $f_1 = 375 \text{ MHz}$, $f_2 = 250 \text{ MHz}$, $f_3 = 150 \text{ MHz}$




Results

- Sender: Linux on Cortex-A53@1.3 GHz
- Transmission delay (APU to REG, per bit): $< 1 \mu s$
- Transmission rate: ~ 122 KBps
- Receiver: Bare metal on Cortex-R5F@533 MHz
- Sampling rate (REG): 497 ns
- Sampling rate (RPU): ~ 2 MSps \rightarrow APU to RPU: 122 KBps

Attack #5: RPU to APU, register-register



Experiments: $f_1 = 375 \text{ MHz}$, $f_2 = 250 \text{ MHz}$, $f_3 = 150 \text{ MHz}$



Results

- Sender: Bare metal on Cortex-R5F@533 MHz
- Transmission delay (RPU to REG, per bit): $457 \text{ ns} \times 2 = 914 \text{ ns}$
- Transmission rate: 133.556 KBps
- Receiver: Linux on Cortex-A53@1.3 GHz
- Sampling rate (REG): $\sim 243 \text{ ns}$
- Sampling rate (APU): $>4 \text{ MSps} \rightarrow \text{RPU to RPU: } \sim 133 \text{ KBps}$

In this talk:


- Covert channels
- The Zynq Ultrascale+ SoC-FPGA
- Frequency and Voltage modulation strategies
- Covert channels between the RPU and the PL
- Covert channels between the APU and the PL
- Covert channels between the APU and the RPU
- Final remarks

To modify the divider registers

- **Bare metal:** Read/write operations over the address.
 - Advantages: High efficiency, unlimited potential
 - Disadvantages: High scrutiny and auditing, requires precise knowledge of the architecture
- **Linux:**
 - Employ the *busybox* utility to *mmap* /dev/mem
 - Similar to a bare metal scenario.
 - Employ the userspace drivers: *cpufreq*, *fclk0*, *fclk1*, *fclk2*, *fclk3*
 - Advantages:
 - Can affect a wide range of architectures
 - Does not require precise knowledge of the system
 - Difficult to detect
 - Disadvantages: Low efficiency

Acknowledgments

The authors acknowledge the support of the French Agence Nationale de la Recherche (ANR), under grant ANR-19-CE39-0008 (project ARCHI-SEC).



<https://archi-sec.telecom-paristech.fr/>



**Laboratoire
Hubert Curien**

**Lilian BOSSUET
Carlos Andres LARA-NINO**